

PRODUCT DATASHEET SMART+ Filament Classic Dimmable 44 6 W/2500 K E27

SMART+ WiFi Filament Classic Dimmable | Classic bulb shape with filament-style with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android™ 8.0 or iOS 14.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- Dimmable
- Lifetime up to 15,000 h
- Light color: Warm White (2,700 K)





TECHNICAL DATA

Electrical data

Naminal wattogo	6 W
Nominal wattage	O VV
Construction wattage	6.00 W
Nominal voltage	220240 V
Nominal current	50 mA
Operating frequency	5060 Hz / 50
Mains frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	44 W
Operating mode	AC Mains

Photometrical data

Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.93
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	540 lm
Luminous flux	540 lm
Luminous efficacy	90 lm/W
Adjustable color temperature	2500 K
Color temperature	2500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



MJT3030 STW8C2SB 2700K

Light technical data

|--|

W/2500 K E27

Starting time	< 0.5 s	
Warm-up time (60 %)	< 0.50 s	
Dimensions & Weight		
Product weight	31.00 g	
Diameter	60.00 mm	
Maximum diameter	60 mm	
Length	105.00 mm	
Width	60.00 mm	
Height	60.00 mm	
Outer bulb [PICOS]	A60	
Lifespan		
Number of switching cycles	100000	
Lifespan	15000 h	
Lumen maintenance at end of service lifetime	e lifetime 0.70	
Colors & materials		
Product color	Light grey	
Product color Femperatures & operating conditions	Light grey	
	Light grey -20+40 °C	
Femperatures & operating conditions		
Femperatures & operating conditions Ambient temperature range		
Temperatures & operating conditions Ambient temperature range Additional product data	-20+40 °C	
Femperatures & operating conditions Ambient temperature range Additional product data Mercury-free	-20+40 °C Yes All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each	
Femperatures & operating conditions Ambient temperature range Additional product data Mercury-free Product remark	Yes All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Temperatures & operating conditions Ambient temperature range Additional product data Mercury-free Product remark Base (standard designation)	Yes All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Femperatures & operating conditions Ambient temperature range Additional product data Mercury-free Product remark Base (standard designation) Capabilities	Yes All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value E27	
Femperatures & operating conditions Ambient temperature range Additional product data Mercury-free Product remark Base (standard designation) Capabilities Dimmable	Yes All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value E27 Yes 1)	
Ambient temperature range Additional product data Mercury-free Product remark Base (standard designation) Capabilities Dimmable Compatible smart home technology	Yes All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value E27 Yes 1)	

Energy consumption	6.00 kWh/1000h
Standards	CE
Type of protection	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.5 W
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.478
Chromaticity coordinate y	0.415
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.50
LED light source replaces a fluorescent light source	No
EPREL ID	644688
Model number	AC32969

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

W/2500 K E27

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Extended installation guide	SH Insert WIFI StartUpG Lamps DIM LDV
PDF	Declarations of conformity	EU Declaration of Conformity – Smart Filament WiFi CL
PDF	EU Data Act	SMART WiFi Lamps and Luminaires

Photometric and lighting design files	Document name
Spectral power distribution	MJT3030 STW8C2SB 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075609815	Folding box 1	66 mm x 96 mm x 154 mm	116.00 g	0.98 dm ³
4058075609822	Shipping box 4	210 mm x 165 mm x 145 mm	577.00 g	5.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.