

# PRODUCT DATASHEET

## LDECO LITE STREET 100 W/3000 K

STREETLIGHT ECO LITE | Streetlights



### Areas of application

- Streets
- Parking
- Parks
- Gardens
- Residential sector

### Product benefits

- Compact design
- Wide range of applications thanks to a large variety of versions
- Easy connection thanks to included wire (50 cm)

### Product features

- Available with wattage: 30 W, 50 W, 100 W and 150 W
- High luminous efficacy: up to 110 lm/W
- Input voltage: 220...240 V
- Color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index  $R_a$ : > 70
- Type of protection: IP65
- Certificate: CB, RoHS



TECHNICAL DATA

Electrical data

Nominal wattage	100.00 W
Nominal voltage	220...240 V
Protection class	I

Photometrical data

Luminous flux	10000 lm
Luminous efficacy	100 lm/W
Color temperature	3000 K
Color rendering index Ra	> 70
Standard deviation of color matching	< 6 sdc <sub>m</sub>
Beam angle	120 °

Dimensions & Weight

Length	455.00 mm
Width	170.00 mm
Height	53.00 mm
Product weight	1760.00 g

LDECO LITE STREET 100W  
WG\_WL

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Cover material	Tempered glass
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP65
Protection class IK (shock resistance)	IK07
Dimmable	No


Mounting type	Side entry
Mounting location	Pole
Application environment	Outdoor
Replaceable light source	No

### Certificates & Standards

Standards	CB / RoHS
Replaceable light source (EPREL)	Not replaceable

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LDECO LITE STREET 30W50W100W150W WG_WL

Photometric and lighting design files		Document name
	IES file (IES)	LDECO LITE STREET 100W 830,840,865 WG 8X1 LEDV

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075568617	Folding box 1	185 mm x 48 mm x 480 mm	2014.00 g	4.26 dm <sup>3</sup>
4058075568624	Shipping box 8	490 mm x 380 mm x 210 mm	17003.00 g	39.10 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.