

PRODUCT DATASHEET

LED VALUE CEILING 30 W 6500 K

LED VALUE CEILING GEN4 | Wall and ceiling luminaires



Areas of application

- Bedrooms
- Dining rooms
- Balcony
- Corridors

Product features

- Protection class: I
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime (L70/B50): up to 30,000 h
- Color consistency: SDCM 5
- Color rendering index R_a : ≥ 80
- Beam angle: 120°
- Surge voltage capability: 1 kV



TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	100...240 V
Mains frequency	50...60 Hz
Nominal current	140.000 mA
Protection class	I

Photometrical data

Luminous flux	2400 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥80
Beam angle	120 °

Dimensions & Weight

Diameter	390.00 mm
Height	70.00 mm
Product weight	777.00 g

LDVAL CEILING 30W 100-240V G4

Materials & Colors

Product color	White
Housing color	White
Body material	Metal
Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

Application & Mounting


Type of connection	Terminal
Type of protection	IP20



Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED VALUE CEILING

Photometric and lighting design files		Document name
	IES file (IES)	LDVALCEILING30W 100-240V G4
	LDT file (Eulumdat)	LDVALCEILING30W 100-240V G4

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075520059	Folding box 1	430 mm x 430 mm x 77 mm	1130.00 g	14.24 dm ³
4058075520066	Shipping box 5	445 mm x 405 mm x 455 mm	6550.00 g	82.00 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.