

# PRODUCT DATASHEET LED ECO LITE FLOODLIGHT 200 W/6500 K

LED ECO LITE FLOODLIGHT G2 | Floodlights



#### Areas of application

- Parking
- Sports facilities
- Billboard lighting
- Public areas

#### **Product benefits**

- Low windage thanks to the compact and slim design
- Cable water stopper protects luminaires against the siphonage
- Texture glass offer a comfortable lighting
- IP65 protection is suitable for outdoor application

#### Product features

- Driver on board technology platform
- $-\,$  Available in 10 W, 20 W, 30 W, 50 W, 100 W, 150 W and 200 W
- Standard CCT: 3000 K & 6500 K
- Color rendering index Ra: > 80
- Power factor: > 0.9
- Luminaire efficacy: up to 80 lm/W
- Lifetime: up to 20,000 h
- Safety compliance certificates: CB, EMC, RoHS 2.0

Page 1 of 3

## TECHNICAL DATA

## Electrical data

Nominal wattage	200.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	0.84 A
Inrush current	2.1 A
Inrush current time T <sub>h50</sub>	6.72 µs
Max. number of luminaires per miniature circuit breaker B16	15
Max. number of luminaires per miniature circuit breaker C16	15
Power factor $\lambda$	0.90
Total harmonic distortion	≤ 20 %
Protection class	I

## Photometrical data

Luminous flux	16000 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Luminous intensity	5800
Photobiological safety group acc. to EN62778	RG1
Beam angle	110°

# Dimensions & Weight

Length	389.00 mm
Width	290.00 mm
Height	52.00 mm
Product weight	2940.00 g
Cable length	0.3 m

## Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-30+45 °C
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	20000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	20000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	20000 h

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Certificates & Standards

Standards	CB / ROHS / EMC
Replaceable light source (EPREL)	Not replaceable

## DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LDECO LITE FL 200W 865

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075729568	Folding box 1	399 mm x 60 mm x 316 mm	3118.00 g	7.57 dm <sup>3</sup>
4058075729575	Shipping box 5	417 mm x 337 mm x 324 mm	16421.00 g	45.53 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.