PRODUCT DATASHEET
IP65 BULKHEAD 24W 830 WT R

IP65 BULKHEAD | Stylish and contemporary designed luminaire, suitable for all outdoor applications

Areas of application

- Public areas
- Gardens
- Pathway lighting
- Outdoor applications
- Corridors, stairways, entrance areas
- Passages, underpasses

Product benefits

- Stylish and modern design

Product features

- Color temperature: 3,000 K, 4,000 K, 6,500 K
- High luminous efficacy: 90 lm/W
- Available in 15W, 20W, 24W
- Type of protection: IP65
- Impact resistance: IK06
- Available in round and oval form
- Color: black or white
- Polypropylene housing
- Lifetime up to 25,000 h

© 2025, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Power factor λ	> 0.90
Protection class	II

Photometrical data

Luminous flux	2000 lm
Total luminous flux of contained light sources	2250 lm
Luminous efficacy	80 lm/W
Color temperature	3000 K
Color rendering index Ra	> 80
Beam angle	120 °

Dimensions & Weight

Diameter	280.00 mm
Height	60.00 mm
Product weight	425.00 g

LDECO BH

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Cover material	Polypropylene (PP)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20…+45 °C
Type of protection	IP65
Dimmable	No
Mounting type	Surface
Application environment	Outdoor

© 2025, LEDVANCE GmbH. All rights reserved.

Replaceable light source	No

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854097294	Folding box 1	282 mm x 66 mm x 282 mm	564.00 g	5.25 dm^3
4099854097300	Shipping box 10	585 mm x 355 mm x 300 mm	6570.00 g	62.30 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2025, LEDVANCE GmbH. All rights reserved.