

PRODUCT DATASHEET IP65 BULKHEAD 15W 830 WT R

IP65 BULKHEAD | Stylish and contemporary designed luminaire, suitable for all outdoor applications



Areas of application

- Public areas
- Gardens
- Pathway lighting
- Outdoor applications
- Corridors, stairways, entrance areas
- Passages, underpasses

Product benefits

- Stylish and modern design

Product features

- Color temperature: 3,000 K, 4,000 K, 6,500 K
- High luminous efficacy: 90 lm/W
- Available in 15W, 20W, 24W
- Type of protection: IP65
- Impact resistance: IK06
- Available in round and oval form
- Color: black or white
- Polypropylene housing
- Lifetime up to 25,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	> 0.90
Protection class	П

Photometrical data

Luminous flux	1200 lm
Total luminous flux of contained light sources	1350 lm
Luminous efficacy	80 lm/W
Color temperature	3000 K
Color rendering index Ra	> 80
Beam angle	120°

Dimensions & Weight

Diameter	180.00 mm
Height	45.00 mm
Product weight	200.00 g

LDECO BH

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Cover material	Polypropylene (PP)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+45 °C
Type of protection	IP65
Dimmable	No
Mounting type	Surface
Application environment	Outdoor

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854096594	Folding box 1	184 mm x 49 mm x 184 mm	245.00 g	1.66 dm ³
4099854096600	Shipping box 20	520 mm x 388 mm x 205 mm	5550.00 g	41.36 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.