

# PRODUCT DATASHEET LED VALUE DAMPPROOF CLASSIC 1500 40W 865

LED VALUE DAMP PROOF CLASSIC | Damp-proof luminaires



## Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines

#### Product benefits

- UV-stabilized polycarbonate opal diffuser for uniform light distribution and long durability
- Classic structural design meets the needs of most customers in the market
- Long lifetime reduces maintenance cost

## **Product features**

- Class I Luminaires
- Available in 3 length options: 600 mm, 1200 mm, 1500 mm
- 3 lumen packages: 16W 1600lm, 32W 3200lm, 40W 4000lm
- Standard CCT: 6500 K and 4000 K
- Lifetime (L70/B50): up to 30,000 h
- Color rendering index R<sub>a</sub>: > 80
- Type of protection: IP65
- Impact resistance: IK08
- Certificate: CB, RoHS

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	40.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	364.000 mA
Protection class	1

## Photometrical data

Luminous flux	4000 lm	
Luminous efficacy	100 lm/W	
Color temperature	6500 K	
Color rendering index Ra	> 80	
Beam angle	120°	

# Dimensions & Weight

Length	1563.00 mm
Width	68.00 mm
Height	67.00 mm
Product weight	1322.00 g



VALUE DP CLASSIC

# Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Plastic
Mercury content	0.0 mg

# **Application & Mounting**

Type of protection	IP65	
Dimmable	No	
Mounting type	Surface/Suspended	
Application environment	Indoor	

Replaceable light source No	lo
-----------------------------	----

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	LDVAL DP UI

Photometric and lighting design files	Document name
IES file (IES)	LDVAL DP 1500 40W 865

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854110504	Folding box 1	71 mm x 69 mm x 1,565 mm	1377.00 g	7.67 dm <sup>3</sup>
4099854110511	Shipping box 8	1,585 mm x 160 mm x 305 mm	12016.00 g	77.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.