

# PRODUCT DATASHEET LED ECO LITE DAMP PROOF HOUSING SE G2 1200

LED ECO LITE DAMPPROOF HOUSING G2 | Damp-proof housing with back-plate



- Industrial and storage facilities
- Car parks
- Garages
- Workshops, assembly lines



# Product benefits

- UV stabilized, impact resistant polycarbonate diffuser and body
- VDE certified components ensure product reliability

### **Product features**

- Lifetime up to 25,000 h
- Protection class: I
- Protection rating: IP65
- Classic design with PC body and PC diffuser
- Back-plate to cover wires

### **TECHNICAL DATA**

### Electrical data

Nominal voltage	100277 V
Mains frequency	5060 Hz
Protection class	1

# Dimensions & Weight

Length	1277.00 mm
Width	109.00 mm
Height	67.00 mm
Product weight	1287.00 g



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)

# **Application & Mounting**

Ambient temperature range	-20+45 °C
Type of protection	IP65
Dimmable	No
Mounting type	Surface/Suspended
Application environment	Indoor
Replaceable light source	No

# DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LDECOLITE DP SE LAMPHOUSING	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854514111	Folding box	112 mm x 69 mm x 1,279 mm	1355.00 g	9.88 dm <sup>3</sup>
4099854514128	Shipping box 8	1,300 mm x 240 mm x 305 mm	11918.00 g	95.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.