

PRODUCT DATASHEET SMART+ Wifi Neon Flex 3M RGB + TW

Smart+ Neon Flex Multicolor | Decorative LED Strips for outdoor use with WiFi technology and homogenious illumination



Areas of application

- Gardens, balconies and other outdoor areas
- Living areas
- Indirect and direct lighting

Product benefits

- Easy and quick installation
- Uses multi color and cold or warm white light for most flexible lighting scenes

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Flexible, bendable LED strips
- Type of protection: IP44



TECHNICAL DATA

Electrical data

| Nominal wattage | 15.00 W |
|------------------------|---------------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 120.000 mA |
| Power factor λ | > 0.5 |
| Protection class | Ш |
| Operating mode | External LED driver |

Photometrical data

| Luminous flux | 520 lm |
|--------------------------------------------------------------|------------|
| Total luminous flux of contained light sources | 1260 lm |
| Luminous efficacy | 35 lm/W |
| Color temperature | 27006500 K |
| Reference control setting of contained light source (Kelvin) | 3500 K |
| Light color (designation) | RGBTW |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | < 6 sdcm |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 110 ° |

Dimensions & Weight

| Length | 3000.00 mm |
|----------------|------------|
| Width | 17.50 mm |
| Height | 9.80 mm |
| Product weight | 670.00 g |

SMART WIFI NEON FLEX 3M RGBTW IP44

Materials & Colors

| Product color | Transparent |
|-----------------|--------------------|
| Body material | Silicone |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -2040 °C |
|---------------------------|------------------|
| Type of connection | Plug type C (EU) |
| Type of protection | IP44 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Surface |
| Mounting location | All surfaces |
| Application environment | Outdoor |
| With light source | Yes |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h |
|----------------------------|---------|
| Number of switching cycles | 15000 |

Certificates & Standards

| Standards | CE / EAC |
|-----------|----------|
| | |

EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

Safety advice

- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by a qualified person in order to avoid a hazard.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.

DOWNLOAD DATA

| Documents and certificates | | Document name | |
|----------------------------|---------------------------------------------------------|------------------------------------|--|
| PDF | User instruction / safety instructions | SMART+ WIFI NEON FLEX | |
| PDF | F Legal information Legal insert residential luminaires | | |
| PDF | Declarations of conformity | SMART WIFI NEON FLEX 3M RGBTW IP44 | |
| PDF | EU Data Act SMART WiFi Lamps and Luminaires | | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075504783 | Folding box 1 | 64 mm x 299 mm x 275 mm | 952.00 g | 5.26 dm ³ |
| 4058075504790 | Shipping box 4 | 570 mm x 314 mm x 168 mm | 4957.00 g | 30.07 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.