

PRODUCT DATASHEET LED ECO STICK 11 W/6500 K B22d

LED ECO STICK | LED lamps, classic stick shape



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

Product benefits

- Low energy consumption
- Attractive lamp appearance

Product features

- LED alternative to conventional lamps
- Mercury-free lamps
- Lifetime: up to 8,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	20 W
Nominal current	88 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.50

Photometrical data

Luminous flux	1050 lm
Nominal useful luminous flux 90°	1050 lm
Luminous efficacy	95 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	200 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	118.00 mm
Diameter	43.00 mm
Maximum diameter	43 mm
Product weight	33.00 g

Temperatures & operating conditions

Ambient temperature range	-20+30 °C

Lifespan

Number of switching cycles	100000	
Additional product data		
Base (standard designation)	B22d	
Mercury content	0.0 mg	
Capabilities		
Dimmable	No	
Certificates & Standards		
Standards	CB / RoHS	
Country-specific categorizations		
Order reference	LECO STICK 11W/	
LOGISTICAL DATA		
Temperature range at storage	-20+80 °C	
Energy labelling regulation data acc EU 2019/2015		
Light source cap-type (or other electric interface)	B22d	
Length	118.00 mm	

LOGISTICAL DATA

Height

Width

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075667334	Folding box	46 mm x 46 mm x 127 mm	46.00 g	0.27 dm ³
4058075667341	Shipping box 10	240 mm x 102 mm x 141 mm	543.00 g	3.45 dm ³

43.00 mm

43.00 mm

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.