

# PRODUCT DATASHEET LED VALUE CLAS A 18 W/3000 K E27

LED VALUE CLASSIC A SURGE PROTECTION | LED lamps, classic bulb shape with surge protection



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

### Product benefits

- Low energy consumption
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

#### **Product features**

- Surge protection: up to 2,000 V
- Lifetime: up to 10,000 h
- Mercury-free lamps



# TECHNICAL DATA

# Electrical data

Nominal wattage	18 W
Construction wattage	18.00 W
Nominal voltage	85250 V
Claimed equiv. conventional lamp power	125 W
Nominal current	148 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	0.50

## Photometrical data

Luminous flux	1800 lm
Nominal useful luminous flux 90°	1800 lm
Luminous efficacy	100 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	80
Light color	830

# Light technical data

Beam angle	180 °
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	150.00 mm
Diameter	80.00 mm
Maximum diameter	90 mm
Product weight	61.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

# Lifespan

Number of switching cycles	100000
----------------------------	--------

# Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg

# Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Type of protection	IP20
Standards	CB / ROHS
Photobiological safety group acc. to EN62778	RG0

# Country-specific categorizations

Order reference	LVCLA 18W/830 8

# LOGISTICAL DATA

Temperature range at storage	-20+80 °C

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	150.00 mm
Height	80.00 mm
Width	80.00 mm

### **DOWNLOAD DATA**

Photometric and lighting design files	Document name
IES file (IES)	LVCLA 18W 830 85-250V FR E27 OSRAM
Light distribution curve type polar	LVCLA 18W 830 85-250V FR E27 OSRAM

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075748958	Folding box 1	80 mm x 80 mm x 150 mm	100.00 g	0.96 dm <sup>3</sup>
4058075748965	Shipping box 10	414 mm x 174 mm x 178 mm	1314.00 g	12.82 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.