

## PRODUCT DATASHEET

### LED ECO PAR16 36 ° 4 W/4000 K GU10

LED ECO PAR16 | LED reflector lamps PAR16 with retrofit pin base



#### Areas of application

- Hospitality
- Restaurants
- Residential interiors

#### Product benefits

- Uniform illumination thanks to TIR-reflector and fly eye single optic design
- Clear cast shadows for brilliant accent light
- Energy savings of up to 93 % (compared to halogen lamps)
- High color homogeneity
- Easy replacement of halogen lamps thanks to compact design
- Quick and simple LED conversion without modification of the existing installation
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### Product features

- High-quality LED replacement for halogen reflector lamps
- High color consistency: < 6 SDCM
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	50 W
Nominal current	42 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

### Photometrical data

Luminous intensity	700 cd
Luminous flux	350 lm
Luminous efficacy	87 lm/W
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>
Rated peak intensity	700 cd

### Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	54.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	19.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	100000
----------------------------	--------

**Additional product data**

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

**Capabilities**

Dimmable	No
----------	----

**Certificates & Standards**

Energy efficiency class	F 1)
-------------------------	------

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

**Country-specific categorizations**

Order reference	LPAR1650 5W/840
-----------------	-----------------


**LOGISTICAL DATA**

Temperature range at storage	-20...+80 °C
------------------------------	--------------

**Energy labelling regulation data acc EU 2019/2015**

Light source cap-type (or other electric interface)	GU10
Length	54.00 mm
Height	50.00 mm
Width	50.00 mm
Displacement factor	>0.7

**DOWNLOAD DATA**

Photometric and lighting design files	Document name
 IES file (IES)	LED ECO PAR16 50 GU10

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075204577	Folding box 1	49 mm x 49 mm x 62 mm	37.00 g	0.15 dm <sup>3</sup>
4058075204584	Shipping box 10	255 mm x 107 mm x 72 mm	420.00 g	1.96 dm <sup>3</sup>
4099854265952	Shipping box 10	255 mm x 107 mm x 72 mm	393.00 g	1.96 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.