

## PRODUCT DATASHEET

# LED PFM PAR16 60 ° 7.5 W/6500 K GU10

LED PERFORMANCE PAR16 | LED reflector lamps PAR16 with retrofit pin base



### Areas of application

- Hospitality
- Restaurants
- Residential interiors
- Museums, art galleries

### Product benefits

- Attractive lamp appearance
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Good quality of light
- Creation of the preferred light ambience thanks to dimming
- Very high dimmer compatibility, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

### Product features

- Single optic design
- Input voltage: 220...240 V<sub>AC</sub>
- Mercury-free lamps
- Lifetime up to 25,000 h
- High color consistency: ≤ 6 SDCM



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	7.5 W
Construction wattage	7.50 W
Nominal voltage	220...240 V
Nominal current	40 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	0.75

### Photometrical data

Luminous flux	675 lm
Luminous efficacy	90 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	90
Light color	965

### Light technical data

Beam angle	60 °
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	52.00 mm
Diameter	50.00 mm
Product weight	39.8 g

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Additional product data

Base (standard designation)	GU10
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Type of protection	IP20
Standards	CB / EMC / RoHS

Country-specific categorizations

Order reference	LPPAR1680607,5W
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	GU10
Length	52.00 mm
Height	50.00 mm
Width	50.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075588271	Folding box 3	155 mm x 53 mm x 89 mm	146.40 g	0.73 dm <sup>3</sup>
4058075588288	Shipping box 24	436 mm x 165 mm x 101 mm	1763.00 g	7.27 dm <sup>3</sup>
4099854262258	Shipping box 24	436 mm x 165 mm x 101 mm	1338.00 g	7.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.