

# PRODUCT DATASHEET LED VALUE CLAS A FIL 7.5 W/4000 K E27 CL

LED VALUE CLASSIC A FILAMENT | LED lamps, classic bulb shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

#### Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Correct operation even at low temperatures

#### **Product features**

- Professional LED lamps for line voltage
- Not dimmable



**E27 CL** 



- Lifetime up to 15,000 h
- Beam angle: up to  $300^{\circ}$
- Lamp made of glass
- Good quality of light; color rendering index  $R_{a}\!\!: \ge 80;$  constant chromaticity

#### TECHNICAL DATA

#### Electrical data

Nominal wattage	7.5 W
Construction wattage	7.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	63 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

#### Photometrical data

Luminous flux	1055 lm
Luminous efficacy	140 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

## Dimensions & Weight

Overall length	106.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	31.00 g

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

#### Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

#### Additional product data

Base (standard designation)	0.0 mg		
Mercury content			
Mercury-free	Yes		
Design / version	Clear		
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		

## Capabilities

Dimmable	No

#### Certificates & Standards

Energy efficiency class	D 1)
Energy consumption	8.00 kWh/1000h
Type of protection	IP20
Standards	CB / ROHS
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

## Country-specific categorizations

Order reference			LV CLA 7,5W/840		
_				F	

#### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Correlated colour temperature type	SINGLE_VALUE
Length	106.00 mm
Height	60.00 mm
Width	60.00 mm
EPREL ID	1402921,1361347
Model number	AC10504,AC45215

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075506527	Folding box 1	64 mm x 64 mm x 131 mm	51.00 g	0.54 dm <sup>3</sup>
4099854259937	Shipping box 10	332 mm x 138 mm x 147 mm	637.00 g	6.73 dm <sup>3</sup>
4058075506534	Shipping box 10	332 mm x 138 mm x 147 mm	667.00 g	6.73 dm <sup>3</sup>
4058075751347	Shipping box 10	332 mm x 138 mm x 147 mm	647.00 g	6.73 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.