

## PRODUCT DATASHEET

### LED VALUE CLAS B FIL 4 W/2700 K B15d GEN2

LED VALUE CLASSIC B FILAMENT | LED lamps, classic mini-candle shape



#### Areas of application

- Decorative applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Perfect for decorative installations

#### Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower thermal output (compared with the standard reference product)
- Can be easily fitted instead of ordinary light bulbs

#### Product features

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity
- Lifetime up to 15,000 h



## TECHNICAL DATA

### Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	36 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor $\lambda$	> 0.40

### Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcn

### Light technical data

Beam angle	300 °
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	98.00 mm
Diameter	45.00 mm
Maximum diameter	35 mm
Product weight	16.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

**Additional product data**

Base (standard designation)	B15d
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

**Capabilities**

Dimmable	No
----------	----

**Certificates & Standards**

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0



**Country-specific categorizations**

Order reference	LV CLB 4W/827 2
-----------------	-----------------

**Energy labelling regulation data acc EU 2019/2015**

Light source cap-type (or other electric interface)	B15d
Length	98.00 mm
Height	45.00 mm
Width	45.00 mm
EPREL ID	734527
Model number	AC36779

**DOWNLOAD DATA**

Photometric and lighting design files		Document name
	IES file (IES)	AC14561 LED VALUE CLB 4 W FIL 2700K G2AU
	LDT file (Eulumdat)	LED VALUE CLAS B FIL 4 W 2700K B15d GEN2

Photometric and lighting design files	Document name
Light distribution curve type polar	LED VALUE CLAS B FIL 4 W 2700K B15d GEN2

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267688	Folding box 1	51 mm x 51 mm x 130 mm	28.00 g	0.34 dm <sup>3</sup>
4058075506459	Shipping box 10	266 mm x 109 mm x 142 mm	425.00 g	4.12 dm <sup>3</sup>
4058075267695	Shipping box 10	266 mm x 109 mm x 142 mm	414.00 g	4.12 dm <sup>3</sup>
4058075750777	Shipping box 10	266 mm x 109 mm x 142 mm	424.00 g	4.12 dm <sup>3</sup>
4099854259975	Shipping box 10	266 mm x 109 mm x 142 mm	415.00 g	4.12 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.