

## PRODUCT DATASHEET

### LED VALUE CLAS P FIL 4 W/4000 K E14 GEN2

LED VALUE CLASSIC P FILAMENT | LED lamps, classic mini-ball shape



#### Areas of application

- Perfect for decorative installations
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Domestic applications

#### Product benefits

- Very low energy consumption
- Lamps with innovative LED "filament" technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

#### Product features



- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Beam angle: up to 300°
- Lifetime up to 15,000 h

## TECHNICAL DATA

### Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	35 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor $\lambda$	> 0.40

### Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcn

### Light technical data

Beam angle	300 °
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	78.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	13.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

**Additional product data**

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

**Capabilities**

Dimmable	No
----------	----

**Certificates & Standards**

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0



**Country-specific categorizations**

Order reference	LV CLP 4W/840 2
-----------------	-----------------

**Energy labelling regulation data acc EU 2019/2015**

Light source cap-type (or other electric interface)	E14
Standby power	0 W
Length	78.00 mm
Height	45.00 mm
Width	45.00 mm
EPREL ID	1403405,523181
Model number	AC24331,AC32370

**DOWNLOAD DATA**

Photometric and lighting design files	Document name
 LDT file (Eulumdat)	3522671 LED VALUE CLAS P GLFR 4 W 4000K E14
 Light distribution curve type polar	3522671 LED VALUE CLAS P GLFR 4 W 4000K E14

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267800	Folding box 1	51 mm x 51 mm x 107 mm	27.00 g	0.28 dm <sup>3</sup>
4058075509245	Shipping box 10	266 mm x 109 mm x 121 mm	396.00 g	3.51 dm <sup>3</sup>
4058075751040	Shipping box 10	266 mm x 109 mm x 121 mm	376.00 g	3.51 dm <sup>3</sup>
4099854260148	Shipping box 10	266 mm x 109 mm x 121 mm	396.00 g	3.51 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.