

PRODUCT DATASHEET LED VALUE CLAS P FIL 4 W/2700 K B22d GEN2

LED VALUE CLASSIC P FILAMENT | LED lamps, classic mini-ball shape



Areas of application

- Perfect for decorative installations
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Domestic applications

Product benefits

- Very low energy consumption
- Lamps with innovative LED "filament" technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

Product features



GFN₂

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Beam angle: up to 300°
- Lifetime up to 15,000 h

GEN2

TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	35 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.40

Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	300 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	83.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	19.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Lifespan

Ni mala an af an Malaban an alaa	100000	
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Additional product data		
Pase (standard designation) B22d		
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Product remark	All technical parameters apply to the entire lamp / Due to the complete production process for light-emitting diodes, the typical values show for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	No	
Certificates & Standards		
Type of protection	IP20	
Photobiological safety group acc. to EN62778		
	RG0	
Country-specific categorizations	RG0	
Country-specific categorizations Order reference	RG0 LV CLP 4W/827 2	
•		
Order reference		
Order reference Energy labelling regulation data acc EU 2019/2015	LV CLP 4W/827 2	
Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface)	LV CLP 4W/827 2 B22d	
Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Standby power	LV CLP 4W/827 2 B22d 0 W	
Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Standby power Length	LV CLP 4W/827 2 B22d 0 W 83.00 mm	

DOWNLOAD DATA

Model number

Photometric and lighting design files	Document name
LDT file (Eulumdat)	3522668 LED VALUE CLAS P GLFR 4 W 2700K B22d
Light distribution curve type polar	3522668 LED VALUE CLAS P GLFR 4 W 2700K B22d

AC24333,AC32372

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267787	Folding box	51 mm x 51 mm x 107 mm	32.00 g	0.28 dm ³
4099854260131	Shipping box 10	266 mm x 109 mm x 121 mm	436.00 g	3.51 dm ³
4058075509221	Shipping box 10	266 mm x 109 mm x 121 mm	446.00 g	3.51 dm ³
4058075267794	Shipping box 10	266 mm x 109 mm x 121 mm	444.00 g	3.51 dm ³
4058075751026	Shipping box 10	266 mm x 109 mm x 121 mm	436.00 g	3.51 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.