

# PRODUCT DATASHEET HAL CL A 57 W 240 V B22d

HALOGEN CLASSIC A | Halogen lamps, classic bulb shape



#### Areas of application

- General illumination
- Mood lighting
- Entrance lighting
- Restaurants, hotels and similar prestigious applications

### Product benefits

- Simple direct replacement for conventional incandescent lamps
- The same pleasant quality of light as that of an incandescent lamp
- Instant 100 % light, no warm-up time
- Contains no mercury
- UV filter

#### **Product features**

- 100 % dimmable
- Perfect color rendering (Ra: 100)
- Average life: 2,000 h

## TECHNICAL DATA

## Electrical data

Nominal wattage	57 W
Construction wattage	57.00 W
Nominal voltage	240 V

## Photometrical data

Luminous flux	915 lm
Luminous efficacy	16 lm/W
Color temperature	2800 K
Color rendering index Ra	100
Light color	1028

# Light technical data

Starting time	0 s
---------------	-----

## Dimensions & Weight

Overall length	96.00 mm
Light center length (LCL)	73,0 mm
Diameter	55.00 mm
Product weight	31.00 g

## Additional product data

Base (standard designation)	B22d
Mercury-free	Yes
Design / version	Bulb

## Capabilities

## Country-specific categorizations

ILCOS	HSGSA/F/UB-57-240-B22D-73
Order reference	64544 ACLAFR 57

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	93.00 mm
Height	55.00 mm
Width	55.00 mm

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

## DOWNLOAD DATA

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321629531	Folding box 1	55 mm x 55 mm x 97 mm	40.00 g	0.29 dm <sup>3</sup>
4008321845238	Shipping box 20	286 mm x 234 mm x 105 mm	895.00 g	7.03 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.