

## PRODUCT DATASHEET

# DST STICK 14 W/4000 K 220...240 V B22d

OSRAM DULUXSTAR® STICK | Compact fluorescent integrated, stick shape



### Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

### Product benefits

- Fast return on investment
- Up to 80 % less energy consumption compared with ordinary light bulbs

### Product features

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h



## TECHNICAL DATA

### Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	220...240 V
Nominal current	140 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor $\lambda$	$\geq 0.55$

### Photometrical data

Luminous flux	800 lm
Luminous efficacy	58 lm/W
Color temperature	4000 K
Color rendering index Ra	$\geq 80$
Light color	840

### Light technical data

Starting time	$\leq 0.3$ s
---------------	--------------

### Dimensions & Weight

Overall length	133.00 mm
Diameter	41.00 mm
Maximum diameter	41 mm
Product weight	65.00 g

### Lifespan

Number of switching cycles	$\geq 10000$
----------------------------	--------------

### Additional product data

Base (standard designation)	B22d
Mercury content	2.0 mg
Mercury-free	No

### Country-specific categorizations

Order reference	DSTAR 14W/840 2
-----------------	-----------------

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	133.00 mm
Height	41.00 mm
Width	41.00 mm

## Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)
- Not for use with external dimmers or electronic switches.

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899449534	Folding box 1	43 mm x 43 mm x 140 mm	83.00 g	0.26 dm <sup>3</sup>
4058075076730	Bundle 10	215 mm x 86 mm x 139 mm	822.00 g	2.57 dm <sup>3</sup>
4052899449541	Shipping box 10	226 mm x 95 mm x 156 mm	921.00 g	3.35 dm <sup>3</sup>
4058075076747	Shipping box 10	226 mm x 95 mm x 156 mm	923.00 g	3.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.