

PRODUCT DATASHEET

DST STICK 14 W/2700 K 220...240 V B22d

OSRAM DULUXSTAR® STICK | Compact fluorescent integrated, stick shape



Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

Product benefits

- Fast return on investment
- Up to 80 % less energy consumption compared with ordinary light bulbs

Product features

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h



TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 14 W |
| Construction wattage | 14.00 W |
| Nominal voltage | 220...240 V |
| Nominal current | 140 mA |
| Operating frequency | 50...60 Hz |
| Mains frequency | 50...60 Hz |
| Power factor λ | ≥ 0.55 |

Photometrical data

| | |
|--------------------------|-----------|
| Luminous flux | 800 lm |
| Luminous efficacy | 58 lm/W |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥ 80 |
| Light color | 827 |

Light technical data

| | |
|---------------|--------------|
| Starting time | ≤ 0.3 s |
|---------------|--------------|

Dimensions & Weight

| | |
|------------------|-----------|
| Overall length | 133.00 mm |
| Diameter | 41.00 mm |
| Maximum diameter | 41 mm |
| Product weight | 65.00 g |

Lifespan

| | |
|----------------------------|--------------|
| Number of switching cycles | ≥ 10000 |
|----------------------------|--------------|

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | B22d |
| Mercury content | 2.0 mg |
| Mercury-free | No |

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | DSTAR 14W/827 2 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|---|-----------|
| Light source cap-type (or other electric interface) | B22d |
| Length | 133.00 mm |
| Height | 41.00 mm |
| Width | 41.00 mm |

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp
- Not for use with external dimmers or electronic switches.

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4052899449510 | Folding box 1 | 43 mm x 43 mm x 140 mm | 83.00 g | 0.26 dm ³ |
| 4058075076693 | Bundle 10 | 215 mm x 86 mm x 139 mm | 822.00 g | 2.57 dm ³ |
| 4058075076709 | Shipping box 10 | 226 mm x 95 mm x 156 mm | 923.00 g | 3.35 dm ³ |
| 4052899449527 | Shipping box 10 | 226 mm x 95 mm x 156 mm | 921.00 g | 3.35 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.