

# PRODUCT DATASHEET DULUX D/E 26 W/865 K G24q-3

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



#### Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

#### Product benefits

- Extremly economical
- Good quality of light

#### **Product features**

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



# TECHNICAL DATA

# Electrical data

Nominal wattage	26 W
Construction wattage	26.00 W

#### Photometrical data

Luminous flux	1710 lm
Light color (designation)	LUMILUX Daylight
Color temperature	865 K
Color rendering index Ra	≥80
Light color	886
Rated LLMF at 2,000 h	0.81
Rated LLMF at 4,000 h	0.76
Rated LLMF at 6,000 h	0.74
Rated LLMF at 8,000 h	0.73
Rated lamp efficacy (standard co.)	66 lm/W

# Dimensions & Weight

Overall length	163.00 mm
Diameter	13.00 mm
Maximum diameter	11 mm
Product weight	49.00 g

# Temperatures & operating conditions

Rated ambient temp.w.max.luminous 25.0 °	0 ℃
------------------------------------------	-----

# Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	HF

# Additional product data

Base (standard designation)	G24q-3
Mercury content	1.3 mg

## Capabilities

Suitable for indoor	Yes
---------------------	-----

## Certificates & Standards

Energy efficiency class	A
Energy consumption	28.60 kWh/1000h

## Country-specific categorizations

Order reference	DULUX D/E 26W/8

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24q-3
Length	165.00 mm
Height	13.00 mm
Width	13.00 mm

#### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic control gear

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830531	Folding box	36 mm x 36 mm x 179 mm	59.00 g	0.23 dm <sup>3</sup>
4008321830548	Shipping box 10	187 mm x 81 mm x 196 mm	919.00 g	2.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.