

PRODUCT DATASHEET

HO 54 W/865

LUMILUX® T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base



Areas of application

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks
- Outdoor applications only in suitable luminaires

Product benefits

- Up to 20 % more economical than LUMILUX® T8

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable




TECHNICAL DATA

Electrical data

Nominal wattage	54 W
Construction wattage	54.10 W
Nominal voltage	120 V
Rated lamp efficacy (HF data 25 °C)	76

Photometrical data

Luminous flux	4100 lm
Luminous efficacy	76 lm/W
Luminous flux at 25 °C	4100 lm
Luminous flux at 35 °C	4750 lm
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.93
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	76



349641_FL_865

Dimensions & Weight

Overall length	1149.00 mm
----------------	------------

Length with base excl. base pins/connection	1149 mm
Diameter	16,0 mm
Tube diameter	16 mm
Maximum diameter	16 mm
Product weight	90.00 g

Temperatures & operating conditions

Rated ambient temp.w.max.luminous	35.0 °C
-----------------------------------	---------

Lifespan

Service life	19000 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.97
Rated lamp survival factor at 20,000 h	0.85
Operation mode LLMF/LSF	HF

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G5
Mercury content	1.7 mg
Product remark	Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C

Capabilities

Suitable for indoor	Yes
Dimmable	Yes

Certificates & Standards

Energy efficiency class	G
Energy consumption	59.51 kWh/1000h

Country-specific categorizations

ILCOS	FDH-54/865-L/P/-G5-16/1149
Order reference	HO 54W/865


Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5
Length	1149.00 mm
Height	16,0 mm
Width	16,0 mm

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

Photometric and lighting design files	Document name
 Spectral power distribution	349641_FL_865

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300453378	Unpacked 1	1,165 mm x 19 mm x 20 mm	113.67 g	0.44 dm ³
4050300453385	Shipping box 40	1,194 mm x 199 mm x 87 mm	4222.00 g	20.67 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.