

# PRODUCT DATASHEET

## L 30 W/640

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	30 W
Construction wattage	30.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

**Photometrical data**

Luminous flux	2100 lm
Luminous efficacy	70 lm/W
Luminous flux at 25 °C	2100 lm
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥60
Light color	640
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

**Dimensions & Weight**

Overall length	895.00 mm
Length with base excl. base pins/connection	895,00 mm
Tube diameter	26 mm
Product weight	124.00 g

**Lifespan**

Service life	5000 h
--------------	--------

**Additional product data**

Base (standard designation)	G13
-----------------------------	-----

**Country-specific categorizations**

ILCOS	FD-30/640-E-G13-26/895
Order reference	L 30W/640

**Energy labelling regulation data acc EU 2019/2015**

Light source cap-type (or other electric interface)	G13
Length	895.00 mm

---

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321959690	Sleeve 1	910 mm x 27 mm x 27 mm	144.00 g	0.66 dm <sup>3</sup>
4008321959799	Shipping box 25	937 mm x 142 mm x 145 mm	3910.00 g	19.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.