

PRODUCT DATASHEET

L 32 W 6000 K G10q

Basic T9 C | Circular fluorescent lamps 29 mm, with G10Q base



TECHNICAL DATA

Electrical data

Nominal wattage	32 W
Construction wattage	32.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	2150 lm
Luminous efficacy	67 lm/W
Luminous flux at 25 °C	2150 lm
Color temperature	6000 K
Color rendering index Ra	80...89
Light color	860
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	304.90 mm
Diameter	29.00 mm
Product weight	192.00 g

Lifespan

Service life	5000 h
--------------	--------

Additional product data

Base (standard designation)	G10q
Mercury content	3.0 mg
Design / version	LUMILUX version

Country-specific categorizations

Order reference	L 32W/640 C G10
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
Length	305.00 mm
Height	29.00 mm
Width	29.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300175669	Sleeve 1	309 mm x 306 mm x 38 mm	322.00 g	3.59 dm ³
4050300175676	Shipping box 12	452 mm x 323 mm x 320 mm	4305.00 g	46.72 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.