

PRODUCT DATASHEET

LED Performance Surface Mount Downlight 30 W 15 ° 4000 K White

LED PERFORMANCE SURFACE MOUNT DOWNLIGHT | LED downlights for ceiling surface mounting



Areas of application

- Shops, supermarkets
- Public areas
- Corridors

Product benefits

- High power COB LED provides high lumen output in compact housing
- Low flicker light thanks to special electronic control gear
- Good color rendering for the best product presentation

Product features

- Available in two housing colors
- Available with color temperature: 3,000 K, 4,000 K
- Color rendering index R_a : > 90
- Power factor: > 0.9
- Initial color consistency: < 5 SDCM
- Lifetime (L70/B50): up to 30,000 h
- Type of protection: IP20
- CCC marked, CB test certificate



TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	2460 lm
Luminous efficacy	82 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	90
Standard deviation of color matching	≤ 5 sdc _m
Beam angle	15 °

Dimensions & Weight

Diameter	134.00 mm
Height	135.00 mm
Product weight	1014.00 g
Cable length	110 mm



SURFACE DOWNLIGHT 30W

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum

Mercury content	0.0 mg
-----------------	--------

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+70 °C
Type of connection	Cable, 2-pole
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor

Lifespan


Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	LDPFM SURF DL IES

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075326170	Folding box 1	140 mm x 140 mm x 140 mm	1099.00 g	2.74 dm ³
4058075326187	Shipping box 8	300 mm x 300 mm x 300 mm	9460.00 g	27.00 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.