

PRODUCT DATASHEET

VALUE BAT 11.00 W 4000 K GEN3

LED VALUE BATTEN | LED batten luminaires



Areas of application

- Contour lighting
- Cove lighting
- Shelf lighting
- Backlighting
- Indoor applications

Product benefits

- Homogeneous light output
- Mercury-free technology

Product features

- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime up to 15,000 h
- Connection with 2-pin plug connection
- Beam angle: 120°
- Luminaire efficacy: up to 80 lm/W
- Power factor: 0.5
- CCC marked, CB test certificate



TECHNICAL DATA

Electrical data


Nominal wattage	11.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	95.000 mA
Power factor λ	0.50
Protection class	II
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	1000 lm
Luminous efficacy	80 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥ 70
Standard deviation of color matching	≤ 7 sdcM
Beam angle	120 °

Dimensions & Weight

Length	985.00 mm
Width	22.20 mm
Height	32.50 mm
Product weight	116.00 g



LDVAL BATTEN 1000 11W G3

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC) Polyvenyl

Cover material	Polycarbonate (PC)
----------------	--------------------

Application & Mounting

Ambient temperature range	-20...+35 °C
Temperature range at storage	-20...+70 °C
Type of protection	IP20
Dimmable	No
Mounting location	Ceiling / Wall
Application environment	Indoor


Lifespan

Number of switching cycles	15000
----------------------------	-------

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LDVAL BAT 1000 11W 4000K G3 APM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075273597	Folding box 1	1,050 mm x 23 mm x 34 mm	181.00 g	0.80 dm ³
4058075273603	Shipping box 24	1,065 mm x 150 mm x 150 mm	5047.00 g	23.96 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.